

**STANDARD FEATURES**

- ◆ 2 hp direct driven single speed motor(s)
- ◆ Adjustable air stream
- ◆ Four blade propeller fan w/OSHA approved inlet guards
- ◆ Aluminized steel cabinet with gray baked on enamel finish
- ◆ Wall mounting bracket with angle adjusting rod
- ◆ Five year parts warranty
- ◆ Crafted with Pride in the USA

**OPTIONAL FEATURE**

- ◆ Weather hood (1) per motor

MODEL	Nozzle Width (in)	Maximum Air Velocity (fpm)	Maximum Air Volume (cfm)	Motor(s) @ hp	Net Wgt (lbs)	Ship Wgt (lbs)
FSX1042A	42	5000	6800	1 @ 2	180	230
FSX1051A	51	5000	7500	1 @ 2	190	240
FSX1066A	66	5000	8400	1 @ 2	205	260
FSX1072A	72	5000	8500	1 @ 2	215	270
FSX2076A	76	5000	13,800	2 @ 2	315	415
FSX2088A	88	5000	14,800	2 @ 2	325	425
FSX2100A	100	5000	15,600	2 @ 2	335	435
FSX2120A	120	5000	17,500	2 @ 2	355	470
FSX3120A	120	5000	20,400	3 @ 2	420	530
FSX3144A	144	5000	22,500	3 @ 2	480	600

For doors wider than 144" - use multiple units.

MOTOR VOLTAGES/AMP DRAWS						
VOLTS	208	240	480	600	190*	380*
PHASE	3	3	3	3	3	3
HERTZ*	60	60	60	60	50	50
AMPS per MOTOR	8.0	7.8	3.9	2.2	2.0	5.5

\*Operation at 50 Hz will generate approximately a 17% reduction in performance.

Sound level measured 10' (3m) from the unit in free field:  
**93 dBA**

*Berner reserves the right alter specifications without prior notice.*